CEMENT PRODUCTION

Energy Storage for Manufacturing and Industrial Decarbonization Workshop "Energy StorM"

February 8, 2022

Dr. Gianluca Ambrosetti CEO, Synhelion SA






Dr. Davide Zampini Head of CEMEX Global R&D



PRODUCTION PROCESS








CLINKER THEMROCHEMISTRY


Cumulated reaction and sensible heat as a function of material temperature. Sensible heat is largely recovered.








TEMPERATURES








ENERGY REQUIREMENTS




Power consumption	Dry process kWh_el/t clinker	Dry process kJ_el/kg clinker	Dry process (%)
Clinker grinding	44.0	158.4	40
Raw materials grinding	22.0	79.2	20
Kiln gear	27.5	99.0	25
Quarry- related consumption (crusher etc.)	16.5	59.4	15
Total	110.0	396.0	







CO₂ GENERATION




3732 kJ/kg clinker Total CO₂: 828 kg/t clinker 62% from calcination






The IR radiation-absorbing (greenhouse) gas is heated by the thermal radiation of the receiver walls and acts as heat transfer fluid (HTF).




- Delivers clean solar process heat at up to 1500°C with receiver efficiency > 80% at moderate solar concentration (~1 MW/m²)
- ⇒ HTF: H₂O vapor or mixtures of H₂O and CO₂ (greenhouse gases)





SOLAR-DRIVEN PYRO-PROCESSING OF CLINKER







THE ENABLING ROLE OF STORAGE

Thermal energy storage (TES)

- o Smoothening of daily fluctuation (cloud
- o Intra-day (at least in spring, summer, and
- ⇒ Reduction of transient (thermal inertia) heat losses in downstream piping (if storage
- → Integration of multiple stochastic sources e.g. electric heat from curtailed renewable



